


NEVER DESCALE AGAIN.

EVER.





- Extends the life of the unit up to three times longer*
- Eliminates the need for regular scale-related maintenance
- No warranty exclusions for hard water
- Maintains "like-new" performance longer

Condensing Features:

- Highly efficient performance
- Outdoor and LP units available
- Ultra-Low NOx emissions

Noncondensing Concentric Vent Features:

- Installs with commercially available venting up to 43'
- Quick natural gas to propane field convertibility
- (kit included with heater)
- Ultra-Low NOx emissions

Model	Height	Width	Depth	Height With Cartridge
ATI-540HX3-N	23-5/8"	17-3/4"	11-1/4"	35-9/16"
ATI-340HX3-N	23-5/8"	17-3/4"	11-1/4"	35-9/16"
ATI-240HX3-N	23-5/8"	17-3/4"	11-1/4"	35-9/16"

Model	Height	Width	Depth	Height With Cartridge
ATI-510CX3	20-1/2"	13-3/4"	11-1/2"	36-1/8"
ATI-310CX3	20-1/2"	13-3/4"	11-1/2"	36-1/8"



Noncondensing concentric vent

Condensing

Unprotected tankless: Failed at 5.8 simulated years and 136,000 gallons



Tankless with X3
Technology:
Still running after 19.7
simulated years
and 460,000 gallons

www.hotwater.com



^{*}Compared to other tankless models without X3 Technology